



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:


UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

December 11, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/519,887
FILING DATE: *November 14, 2003*
RELATED PCT APPLICATION NUMBER: *PCT/US04/38130*

Certified by



Jon W Dudas

Acting Under Secretary of Commerce
for Intellectual Property
and Acting Director of the U.S.
Patent and Trademark Office



BEST AVAILABLE COPY

TITLE

Deep Well Irrigation Pump

DESCRIPTION

Aspects, features and advantages of exemplary embodiments of the present invention (i.e., deep well pump) will become better understood with regard to the following description in connection with the accompanying drawing(s). It should be apparent to those skilled in the art that the described embodiments of the present invention provided herein are illustrative only and not limiting, having been presented by way of example only. All features disclosed in this description may be replaced by alternative features serving the same or similar purpose, unless expressly stated otherwise. Therefore, numerous other embodiments of the modifications thereof are contemplated as falling within the scope of the present invention as defined herein and equivalents thereto. Hence, use of absolute terms, such as, for example, “will,” “will not,” “shall,” “shall not,” “must,” and “must not,” are not meant to limit the scope of the present invention as the embodiments disclosed herein are merely exemplary.

Operation of the Pump

The pump is operated by repeatedly driving the top piston up and down while the bottom cylinder and check valve are submersed in a fluid. The fluid is pulled into the bottom check valve on the up stroke and is forced out of the outlet pipe under pressure during the down stroke. The two pistons are connected by a flexible tension member (rope, cable chain) that pulls up the bottom piston on the up stroke and then gravity returns the bottom

piston to place on the down stroke. The present pump design is driven by two foot operated treadles like a small stair master machine.

Key Features:

Long Loose Leaky Piston:

This design employs two “long loose leaky pistons” that when reciprocated up and down in the cylinder, displace a volume of fluid and create a pressure head. The loose fit between the piston and the cylinder accommodates extremely loose dimensional tolerances (like those found in the inconsistent pipes that are available in many developing countries) and also has many other advantages listed below. Instead of having a tight fitting seal between the piston and cylinder they are both made of cylindrical pipes with the outer diameter of the piston being slightly smaller (up to a few % of the diameter) than the inner diameter of the cylinder. As the piston moves, the length of the piston creates a tortuous leak path making a hydrodynamic seal and allowing the piston to pressurize the fluid. The longer the piston, and the smaller the gap the more efficient this seal becomes.

The advantages of a “long-loose leaky piston” over other pistons are:

- (1) There is very little friction between the piston and cylinder and this friction does not vary much with depth of pumping. The gap between the piston and cylinder is filled with fluid making them hydro-dynamically lubricated. In a normal piston and cylinder pump there is a piston cup (often leather or rubber) where the sealing force and thus the frictional force increases linearly with the depth of the pumping

and greatly increases the pumping forces required. This new pump can thus be very energy efficient compared to a normal piston and cylinder pump.

- (2) The hydrodynamic lubrication means that for clean fluids there is almost no problem with wear on either the piston or cylinder unlike for traditional piston pumps where wear is a major issue and requires the cylinder to be made of hardened material and the piston ring/cup to be replaced on a regular basis. (friction and wear are of-course closely related in this instance).
- (3) Because there is no physical contact between the piston and cylinder the force required to lower the piston is also greatly reduced - it is now only the hydrodynamic drag thru the valve and this allows us to rely on gravity to lower the piston. In regular piston cylinder pumps piston rods are required to push the piston down (to overcome the frictional forces between the piston cup and the cylinder) on the return stroke.
- (4) Because the leaky piston has a substantial leak path the pumping efficiency of the pump is highly velocity dependent (unlike for a traditional piston and cylinder pump). The faster the piston moves the more efficient the pump becomes. (And it also turns out that the longer the stroke the more efficient the pump becomes since less time is taken with the valves open between strokes and the water has to be re-accelerated fewer times - but this last point is also true on traditional piston pumps).

(5) Pumping efficiency is also dependent on the cylinder-piston gap and on the length of the piston (length of the leak path). A longer piston and tighter gap decreases the leakage and increases the volumetric efficiency but also increases the hydrodynamic drag so eventually in the limit it also decreases the energy efficiency. In a normal piston and cylinder pump the volumetric efficiency is pretty much constant (because the tight seal between piston and cylinder) while the energy efficiency decreases with depth of pumping because of greatly increased frictional losses.

(6) A leaky piston is also much less dependent on precise dimensional tolerances between the piston and cylinder compared to a traditional piston pump, and also the surface quality of the cylinder (which usually has to be a very smooth machined surface) is no longer such a major issue. This means that a pump with a leaky piston can be made from fairly rough materials. However, dimensional straightness over the length of the piston and cylinder is still critical. This low need for exact tolerances means that it is possible for the pumping pipe to also act as the cylinder/cylinders, which is another big advantage of the design.

Cable Drive:

This design uses a flexible cable drive (could also be chain, rope, wire, or some other flexible member). Most reciprocating deep well pumps use a rigid driving rod that can push the piston down (and pull it up). This requires more material, and bearing

infrastructure to prevent the rod from buckling. We are using gravity to return the bottom piston to its bottom position—a much cheaper, easier to assemble/transport, and reliable solution. As explained above this is because there is no contact so no real drag between the piston and the cylinder.

Top Piston and Bottom Piston:

We have enabled a pressure head above ground (which is very important for many applications including irrigation) by adding the top leaky piston without any additional valves (other than the two check valves in the bottom cylinder and piston). On the pressure stroke (forcing the top piston down), water is pressurized against the existing bottom check valve and out the outlet at the top of the well. This design reduces the number of valves and seals.

It turns out, however, that the addition of another one-way outlet valve in the outlet pipe increases the efficiency of the pump. Without this extra valve the bottom loose piston gap sees the full (below ground and above ground) pressure head on the up stroke and it leaks a lot more and reduces efficiency. The latest design uses an outside sleeve over the top cylinder with an outlet pipe only at the top end of it, instead of an outlet pipe at the bottom of the top cylinder. This is a very nice addition because it keeps the overall diameter of the down hole components to a minimum allowing the pump to be used in a small diameter bore hole. This is one of the novelty features this patent application claims.

Alternative embodiments of the current design


Several alternative embodiments of the current design include:

1. A pump could be constructed with only the bottom leaky piston and a flexible tension member (rope, cable chain, etc) pulling it up and letting it drop by gravity.
A pump can be built without the top leaky piston and without the outlet pipe.
2. Any type of drive mechanism could be connected to the pump mechanism, including but not limited to other manual drives, a gasoline engine or electric motor.
3. A flexible piston option would work in the case where there is a non-straight cylinder. Here the hydrodynamic pressure would act to ensure that the piston flexes so that it won't get jammed in the cylinder. This would be very useful for pumping fluids through curved pipes.
4. A double reciprocating piston pump (with two pistons one above the other operating 180 degrees out of synch) may be used, with two cables going down the pumping tube.
5. Any type of valve could be used.

Variable Mechanical Advantage:

We have shown that the addition of a variable mechanical advantage on the drive mechanism giving a high mechanical advantage at the start of each stroke (allowing for increased acceleration) and a low mechanical advantage at the end of each stroke (allowing for increased velocity) will maximize the average piston velocity over the

stroke and increase the overall energy efficiency of the pump. This is an attractive feature for a human powered pump.



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. **EU352263059US**

INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
Martin J.		Fisher		USA	
Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
Deep Well Irrigation Pump					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input checked="" type="checkbox"/> Customer Number: 24964					
OR					
<input type="checkbox"/> Firm or Individual Name					
Address					
Address					
City		State		Zip	
Country		Telephone		Fax	
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages <u>7</u>		<input type="checkbox"/> CD(s), Number _____			
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets <u>1</u>		<input checked="" type="checkbox"/> Other (specify) <u>Return Receipt Postcard</u> <i>Certificate of Express Mailing</i>			
<input type="checkbox"/> Application Date Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE Amount (\$)	
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees.				<div style="border: 1px solid black; padding: 10px; text-align: center;">\$80.00</div>	
<input checked="" type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: <u>06-0923</u>					
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

 31281 USPTO
60/519887


(Page 1 of 2)

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME Patrice A. KingTELEPHONE 973-992-1990Date November 14, 2003REGISTRATION NO. 44,833

(if appropriate)

Docket Number: 099997-662-PRO**USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT**

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

 11/19/2003 JALINAH 00000018 060923 60519887
 Sale Ref: 00000053 DAH: 060923 60519887

01 FC:2005

60.00 DA

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PROVISIONAL APPLICATION COVER SHEET
Additional Pag

PTO/SB/16 (08-03)

Approved for use through 07/31/2006. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Docket Number 099997-662-PRO

INVENTOR(S)/APPLICANT(S)		
Given Name (first and middle [if any])	Family or Surname	Residence (City and either State or Foreign Country)
Lawrence E.	Carlson	Boulder, CO
Ben	Tarbell	East Palo Alto, CA
Jonathan I.	Kaplan	Palo Alto, CA
Opher Doron	Yom-Tov	San Francisco, CA
Ari T.	Adler	San Francisco, CA
Christine M.	Kurjan	Mountain View, Ca
Robert Ian	Lister	Great Britain
Shilajett	Banerjee	Belmot, CA

[Page 2 of 2]

Number 2 of 2

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

CERTIFICATE OF EXPRESS MAILING

EXPRESS MAIL Mailing Label Number EU352263062US


Deposited: November 14, 2003

I hereby certify that this and the enclosed paper(s) and/or fee(s) is/are being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" service under 37 CFR §1.10 on the date indicated above and is addressed to: Commissioner for Patents; P.O. Box 1450, Alexandria, VA 22313-1450, Mail Stop Provisional Application.

Submitted herewith are the following items:

- 1) Provisional Application for Patent Cover Sheet;
- 2) Specification and Drawings (if applicable);
- 3) Certificate of Express Mailing (Express Mail Number EU352263059US); and
- 4) Return Receipt Postcard

TOTAL PAGES IN THIS SUBMISSION: 11


Yvette Alvarez-Perez

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/038130

International filing date: 15 November 2004 (15.11.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/519,887
Filing date: 14 November 2003 (14.11.2003)

Date of receipt at the International Bureau: 17 December 2004 (17.12.2004)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record.

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:



☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**



☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**



☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.